

# C942

## Specifications

<b>Performance</b>		
Print Speed <sup>1</sup>	Color/Mono	Up to 50 ppm Letter, 27 ppm Tabloid
Time to First Page <sup>1</sup>	CMYK/Mono	Approx. 8 seconds
Duty Cycle	Max Per Month	300,000 pages
<b>Print Quality</b>	Resolution	Up to 1200 x 1200 dpi; ProQ 1200 x 600 x 16 levels
<b>Memory</b>	RAM (Standard/Max)	2 GB
	Processor	1.2 GHz ARM CPU
<b>Compatibility</b>	Printer Languages	Adobe® PostScript® 3TM, PCL® 6, PCL 5c, XPS®
	Connectivity	Print Speed <sup>1</sup>
	Operating Systems	Windows® and 8.1 support, Windows Vista®, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2: Mac®OS 10.3.9 – 10.10
	Network Protocols	TCP/IP, EtherTalk
<b>Color Features/Solutions</b>		Optional external PC-based RIP: Global Graphics® Harlequin® MultiRIP™ 10, EFI® XF Server or EFI® Fiery FS150 Pro Standard Adobe PostScript 3 controller includes Trapping, ICC-based Color Management, Simulations for SWOP, ISO Coated, Japan Color; PDF Direct Print; PS Gamma Adjust; Color Correct
<b>Print Management</b>		Print Job Accounting; PrintSuperVision 4.0
<b>Media Handling</b>	Media Sizes	Tabloid extra (12" x 18"), tabloid (11" x 17"), legal, letter, executive, 3" x 5" index cards, A3, A4, A5, A6, B5, C5, DL, Com 10, Monarch envelopes, and banners (up to 13" x 52")
	Media Weight	Trays 1/2/3 and High-Capacity Feeder: 52–320 gsm; Multi-purpose Tray: 52–360 gsm
<b>Media Capacity</b>	Multi-purpose Tray (MPT)	Up to 300 sheets
	Trays 1/2/3	Up to 530 sheets
	High-Capacity Feeder	Up to 1,590 sheets
<b>Max Capacity</b>		Up to 2,950 sheets (w/ MPT, 2 Trays and High-Capacity Feeder)
<b>Media Output</b>		Face Down: max 610 sheets; Face Up: max 300 sheets
<b>Environmental</b>	Size (WxDxH)	27.5" x 24.6" x 25.2" (699 mm x 625 mm x 640mm)
	Weight	244 lb. (110.8kg) including consumables
	Temperature/Humidity	50°– 90° F (10° – 32°C) / 20% – 80%RH
	Power Consumption	Active: 1600W max. /1100W avg.; Standby: avg. 40W; PowerSave mode: 30W or less; Sleep mode: 4W or less; Auto Shutoff: 0.4W or less
	Noise Levels	Active: 57dBA or less; Standby: 34dBA or less; PowerSave mode: Inaudible
	ENERGY STAR® Compliance	Yes
<b>Options</b>	Accessory (Part Number)	530-Sheet 2nd/3rd Tray (45530702); High-Capacity Feeder w/ caster base (45530802); 530-Sheet Tray w/ Caster Base (45530902); Cabinet (70065701); 160 GB Hard Disk Drive (44622302); Harlequin MultiRIP 10 (70066201); EFI XF Server (45592302); EFI Fiery FS150 Pro (Part# TBD)
<b>Warranty</b>	Limited	1-Year On-Site <sup>3</sup> ; 5-Year Digital LED Printheads

## Ordering Information

Product	Description	Part Number
<b>C942</b>	5 – Station Digital LED	62446401
<b>Toner: CMK</b>	38,000 pages <sup>2</sup>	Cyan – 45536515; Magenta – 45536514; Black – 45536516
<b>Toner: Yellow</b>	24,000 pages <sup>2</sup>	Yellow – 45536438
<b>Toner: White</b>	15,000 pages <sup>2</sup>	White – 45536542
<b>Image Drum: CMK</b>	40,000 pages <sup>4</sup>	Cyan – 45103727; Magenta – 45103726; Black – 45103728
<b>Image Drum: Yellow</b>	40,000 pages <sup>4</sup>	Yellow – 45103725
<b>Image Drum: White</b>	20,000 pages <sup>4</sup>	White – 45103764
<b>Waste Toner Box</b>	Approx. 40,000 pages <sup>4</sup>	45531502
<b>Fuser</b>	Approx. 150,000 pages	45531112
<b>Transfer Belt</b>	Approx. 150,000 pages	45531222

<sup>1</sup> Published performance results based on laboratory testing of letter-size sheets, simplex. Individual results may vary.

<sup>2</sup> Based on ISO/IEC 19798

<sup>3</sup> White toner yield based on 5% coverage of letter-size sheet, simplex.

<sup>4</sup> Available in the U.S. and Canada only.

<sup>5</sup> Estimated life based on 3 pages per job.

(single sided letter-size long edge feed)

<sup>6</sup> Fastest CMYK+White digital toner based printer in the 40 ppm - 50 ppm category.



### OKI DATA AMERICAS, INC.

#### USA

2000 BISHOPS GATE BLVD.  
MOUNT LAUREL, NJ 08054-4620  
TEL: 800.OKI.DATA (800.654.3282)  
FAX: 856.222.5320

[WWW.OKIDATA.COM](http://WWW.OKIDATA.COM)

#### CANADA

4140B SLADEVIEW CRESCENT  
UNITS 7 & 8  
MISSISSAUGA, ONTARIO L5L 6A1  
TEL: 905.608.5000  
FAX: 905.608.5040

Specifications are subject to change without notice.

© 2015 Oki Data Americas, Inc. OKI Reg. T.M., M.D., Oki Electric Industry Co., Ltd. Single Pass Color T.M., Oki Data Corp. PANTONE Reg. T.M., Pantone Inc. Harlequin Reg. T.M., Harlequin mark, MultiRIP T.M., Global Graphics Software Ltd. EFI, Fiery Reg. T.M., EFI, Inc. Adobe, PostScript Reg. T.M., PostScript 3 T.M., Adobe Systems, Inc. PCL Reg. T.M., Hewlett-Packard Co. Windows, Windows Vista Reg. T.M., Microsoft Corp. XPS Reg. T.M., Dell, Inc. Mac Reg T.M., Apple Inc. ENERGY STAR Reg. T.M., Reg. T.M., US EPA.